

T1561 Digital Audio Switch DAS 11



Compact and Cost Effective

Tait has significantly reduced the cost and space required for a Digital Audio Switch (DAS II) in a multi-site trunked radio system

DAS \emph{II} is a high density full duplex, non-blocking digital audio switch which packs more features into one-twelfth of the cabinet space of the previous switch.

Up to 64 analogue or 16 digital E1/T1 ports can now be housed in one 4U, 19" rack bin.

In addition to reducing cost and size, DAS *II* offers extra value by including 64 conference channels capable of supporting group calls ranging in size from two simultaneous 30-site group calls to 20 simultaneous three-site group calls.

DAS II can provide end-to-end digital circuit based linking for larger systems. This improves voice clarity, increases system reliability and reduces linking costs.

Other DAS *II* features available include hot plugability of all port cards, and the ability to remotely download software and reconfigure the DAS on the fly without the need to restart the node.*

Port interfaces include:

- Two-wire analogue with DTMF signalling for PSTN/PABX interfaces;
- Four-wire analogue E&M port with DTMF or MFC-R2 signalling for PSTN/PABX interfaces;
- Four-wire analogue (non-signalled) ports for switching inter-site audio lines;
- E1/T1 digital port for inter-site and inter-node audio and data transport switching.
- Asynchronous data port for transporting system control data between site and nodes, or between nodes on an E1/T1 link.



^{*}Check with your Tait Dealer for availability



General Specifications

CORPORATE HEAD OFFICE NEW ZEALAND Tait Electronics Ltd P O Box 1645, Christchurch

AUSTRALIA

Tait Electronics (Aust) Pty Ltd Toll Free: 1-300 304 344 E-mail: australia@taitworld.com

TAIT NORTH AMERICA INC.

Regional Head Office CANADA

Toll Free: 1-800-890 TAIT (8248) E-mail: canada@taitworld.com

USA

Toll Free: 1-800-890 TAIT (8248) E-mail: usa@taitworld.com

LATIN AMERICA

Tait Latin America E-mail: latinamerica@taitworld.com

NEW ZEALAND

Tait Communications Ltd E-mail: headoffice@tcl.tait.co.nz

TAIT EUROPE LTD

Regional Head Office UNITED KINGDOM Tait Mobile Radio Ltd

E-mail: united kingdom@taitworld.com

FRANCE

Antenne Française

E-mail: france@taitworld.com

GERMANY

Zweigstelle Deutschland E-mail: germany@taitworld.com

TAIT NORTH ASIA

Regional Head Office HONG KONG

Tait Mobile Radio (Hong Kong) Ltd E-mail: hongkong@taitworld.com

BEIJING

Tait Mobile Radio (Hong Kong) Ltd

E-mail: beijing@taitworld.com

TAIWAN

Tait Mobile Radio (Taiwan) Ltd

E-mail: taiwan@taitworld.com

TAIT SOUTH EAST ASIA

Regional Head Office SINGAPORE Tait Electronics (Far East) Pte Ltd E-mail: singapore@taitworld.com


THAILAND

Tait Mobile Radio Ltd

E-mail: thailand@taitworld.com

Switch Capacity	512 connections (Current T1540 and T1541 nodes support a maximum of 250 ports)
Conference Capacity	64 software based conference channels provide a mix of conference sizes from 2 simultaneous 30-party conferences to 20 simultaneous 3-party conferences
Bin Capacity	64 analogue ports or 512 digital connections
Bin Size	4U, 19" rack mount
Analogue Ports	4-wire, 600 Ohm balanced leased line interface with no line signalling
	4-wire, 600 Ohm balanced with E&M line interface with both DTMF and MFC-R2 Register signalling
	2-wire, POTS interface with DTMF line signalling
Digital Ports	Primary rate E1/T1 interface with no line signalling
	Asynchronous data interface providing data

transport over E1/T1 time slots



Typical configuration required to support up to 256 ports in a wide area node

Tait is your complete supplier of radio communications equipment, with mobile, portable and infrastructure solutions. Our experience spans 30 years, covering off-the-shelf and customised products, single-site systems and complete turnkey solutions.

